

BANG & OLUFSEN


BEOCORD 8002

HOW TO OPERATE BEOCORD 8002


Survey	2
Tape playback	4
Playing time	4
Automatic search	5
Recording	6
Headphones	7
Programming the timer	8

SETTING UP

Setting up and connecting	8
Presetting the timer	9
Microphone and AUX	9
Maintenance	10
International guarantee	11




- | | |
|--|---|
| <ul style="list-style-type: none"> 1. EJECT, opening the cassette holder 2. Headphone volume control 3. TIMER START, programming the tape start-time 4. REC OPEN, ready-to-record 5. DOLBY NR switch 6. TIMER STOP, programming the tape stop-time 7. TIME SET, presetting the clock 8. MP, metal tape | <ul style="list-style-type: none"> 9. Recording level, left channel 10. Recording level, right channel 11. PROGRAMMING, opening the holder panel 12. Light indicator REC OPEN 13. Peak Programme Meter, drive indicator 14. Light indicator RECORD 15. Light indicator MEMORY 16. Tape position indicator and timer 17. Headphone socket |
|--|---|



- 18. Microphone and auxiliary socket
- 19. Selector switch: radio/amplifier; mic. or aux.
- 20. STAND-BY switch
- 21. RETURN, erasure of already begun recordings
- 22. Rewind
- 23. RECORD, recording pushbutton
- 24. STOP
- 25. Forward

- 26. MEMORY+, activation of the memory function
- 27. MEMORY-, deactivation of the memory function
- 28. Fast forward
- 29. Programming 0 to 9
- 30. CE, programme cancellation
- 31. GO, end of instruction.



TAPE PLAYBACK

Place the connected radio or amplifier in the TAPE mode.

Pressing **[EJECT]** will cause both the large metal cover and the cassette holder to open. Insert the tape cassette into the holder and press down.


Tape type adjustment for ferro, chrome or metal tape is automatic.

Metal

If the rear edge of the cassette does not have holes for metal, the indicator light MP ON will not light automatically. Press METAL ON-OFF.

Start playback

Press **[>]**.



Pause or stop

Press the **[STOP]** pushbutton.

Playback will recommence from the same position on the tape when **[>]** is pressed anew.

Automatic stop

The tape will stop automatically at the conclusion of playback; this also holds true for forward- and rewind.

Forward wind

Press **[>>]**.

Stop: press **[STOP]**.


Rewind

Press **[<<]**.

Stop: press **[STOP]**.

Pushbuttons **[>>]**, **[<<]** and

[>] may be pressed in arbitrary sequence and without the need for pressing **[STOP]** within the sequence.



PLAYING TIME




Most tape recorders incorporate a tape position indicator that displays an arbitrary multi-digit number – a number that has no direct relation to real time.

Beocord 8002 features a tape position indicator that displays tape playback time in minutes and seconds. This allows you to note the virtual playback time of your cassettes.

The position indicator will begin automatically at 0:00 when a tape cassette is inserted – regardless of how large a portion of the tape has been wound. As long as the first digit flashes, – as shown in the photo – forward wind and rewind will shift 0:00 to that tape position corresponding to where/when you have pressed the **[STOP]** pushbutton.

This means that you can – during the interval of the first few (max. 3 minutes) moments – shift 0:00 tape reeling.

As soon as you have read-out 4 digits, say, 00:50, the counter will lock and an eventual rewind to below position 00:00 will reverse the counter and cause it to run in reverse – much the same as a thermometer that shows a temperature below the freezing point. A point will appear before the number when this occurs – as shown in the photo.



Actual playback time

To achieve maximum utilization of the tape position indicator, time should be measured from the very beginning of the cassette tape.

The time calibration is based on cassettes with the following tape thickness:

C 60 18 μm , C 90 12 μm and C 120 9 μm .

When the Beocord 8002 indicates virtual tape time, a precondition is that the recorder must first itself be cognizent of what tape has been inserted – for example, C60 or C90. For this reason the tape will wind forward/reverse several times, automatically. When the correct position is found, two dots (:) will appear midway between the second and third of the four digits.

Two different procedures may be utilized, namely:

Automatic playback from tape beginning

Press **[0]** and **[GO]**.

Automatic playback from the tape position when cassette was inserted

Press **[GO]**.

Elapsed time is measured from the beginning of the tape.

The tape will automatically reel to that tape position where the cassette was inserted, playback will then commence.

AUTOMATIC SEARCH

If – as an example – a particular recording is begun 3 minutes and 30 seconds from the beginning of the tape: Press **[3]** **[3]** **[0]** and **[GO]**.

The Beocord 8002 will automatically wind to the position desired and then begin playback. Playback will begin 8 seconds before the selected time to ensure that the full recording is reproduced.

If, however, you should wish to stop the tape after 3 minutes and 30 seconds, hold down the **[GO]** pushbutton for at least 2 seconds, i.e.




– until the first digits display the pattern shown in this photo.

Incorrect operation

If you press the wrong control and instruct the Beocord 8002 to do something impossible, the pattern shown in this photo will appear.

Cancellation

If you have keyed-in the wrong digit(s), press **[CE]**.



MEMORY

MEMORY+ allows you to introduce a stop point which will function when you actuate **>>** or **<<**, but not the **>** pushbutton.

If, for instance, you have wound to the beginning of a selection of music – a selection you wish to find again in the future:

Press **MEMORY+**.

A light indicator will flash "MEMORY", when you reel either towards, or away from the memory tape position and when the reeling ceases at the desired position.

"MEMORY" will light without interruption in other recorder functions.

Stop-position may be shifted by simply pressing **MEMORY+** anew.

MEMORY is cancelled by pressing **MEMORY-**.

Dolby NR*, noise reduction system

Place the DOLBY NR switch to ON when you playback a Dolby NR recording and when you wish to record with Dolby NR.

Removing a tape cassette

Press **EJECT**, regardless of what particular function the Beocord 8002 happens to be operating in.

RECORDING

Insert a cassette into the cassette holder and press **REC.OPEN**.

This pushbutton is your assurance that you do not unintentionally record on a tape and thus erase selections recorded earlier.

A light indicator will show REC. OPEN and if the tape cassette is itself secured against recording – the tabs at the rear of the cassette have been removed – the position indicator will flicker three times (the pattern shown in the photo) to inform you that recording onto this particular cassette can not take place.

This function will be cancelled if **REC.OPEN** is pressed.

Tape type

Tape type adjustment for ferric, chrome or metal tape takes place automatically when you insert the cassette. With metal tape the METAL ON indicator lights up. If the rear edge of the cassette does not have holes for metal, press METAL ON-OFF. The Beocord 8002 is adjusted to the following tape types:

Ferric: IEC standard, e.g. BASF LH1

Chrome: TDK-SA.

Metal: Scotch Metafine.

Other makes of good quality tape can be used without affecting reproduction significantly.

Improved recording dynamics


The Beocord 8002 employs the Dolby HX Professional recording system, developed jointly by Bang & Olufsen and Dolby Laboratories.

This system allows us to make better use of the dynamic range of each tape. So that by recording with the Beocord, your ferric tapes, whether new or old, can sound like chrome tapes.

Music with a lot of high notes can be recorded at higher levels before distortion occurs. With ferric and chrome tapes you get a signal content which approaches that of metal tape. Also the recording of low notes is clearer, because the side effects of simultaneous loud high notes are eliminated.

The system operates continuously during recording; it requires no manual control.

Tapes recorded on the Beocord 8002 have the same improved sound quality when played back on other cassette recorders – clearer, truer reproduction of all frequencies, and better dynamics.



Preparing to record

Choose programme on radio or amplifier. Press **RECORD**. The Beocord is now in recording-pause position, indicated by RECORD light flashing.

Peak Programme Meter

Now you can adjust the recording volume with reference to the PPM reading. Move the two REC slider controls until the loud music passages give a PPM reading 0 – +2 dB. This applies to all types of tape, with or without DOLBY NR.


The PPM is designed to take into account the tape's signal receptivity, particularly in the treble range.

You get the full benefit of Dolby NR with music passages which give PPM readings below –20 dB. If the music is continuously in the +2 to –20 dB range then Dolby NR remains inoperative.

Recording start

When you are ready to record, press **RECORD** again.

The RECORD indicator now lights steadily, indicating that recording is in progress.



Stop or pause

Press **STOP**.

The tape will not halt instantaneously: A pause of approx. 4 seconds is automatically introduced to ensure a brief interval between recordings.

Extended recording pause

The 4-second pause between two recorded selections may be extended by merely holding down **STOP** when you go from recording to pause.


Continued operation

Recording continues or starts again if the **RECORD** pushbutton is pressed.

Automatic "regret" function

If you should change your mind and no longer wish to record the programme you have begun, then press **RETURN**. Recording will stop and the tape will reel back to the starting point corresponding to that before recording began (the previous recording pause).




RETURN function – rewind to the preceding recording pause – may also be employed after the **STOP** pushbutton has been used.



HEADPHONES

Stereo headphones may be connected to the PHONES socket on the front panel edge of the tape recorder. Adjust volume level with the separate PHONES slider control, found under the metal panel lid.

Headphones may be used during recording as well as during playback.



TIMER PROGRAMMING

Programming for tape playback

If – for instance – you wish to listen to a tape at 12.30 hours: Reel the tape to the desired programme selection position.

Caution: the REC. OPEN light indicator must **not** show light. If it does, press **REC. OPEN** followed by **TIMER START**, **1** **2** **3** **0** **GO**.

The tape position indicator shows the desired time and will then return to display playing time.

Press **STAND BY**.

Programming for unattended recording

If – as an example – you wish to record a radio broadcast at 13.00 hours:

Wind the tape to the point at which the recording is to be stored. Check that REC. OPEN indicator is lit; press **REC. OPEN** if required.

Tune in the radio receiver to the desired programme and adjust the RECORD slider control to that level you use to record radio programmes.

Now press **TIMER START**, **1** **3** **0** **0** **GO**.

The tape position indicator will now show the desired hour and will then return to display playing time.

Press **STAND BY**.

Programming for stop

If – for example – you wish the Beocord 8002 to go to stand by at 14.00 hours: Whether the tape recorder is in the process of recording or playback at that particular time, has no bearing. Press **TIMER STOP**, **1** **4** **0** **0** **GO**.

Check

You may at any arbitrary point in time check the programme status of the Beocord 8002:

Press **TIMER START**. The first digits should flash.

Press **TIMER STOP**. The last digits should flash.

Cancelling

If you do not wish to make use of an existing programme you may cancel it in the following manner:

Press **TIMER START**, **0**, **GO**, or **TIMER STOP**, **0**, **GO**.

STAND BY

When not in use, the Beocord 8002 may be turned off by pressing **STAND BY**.

Automatic stand by




Beocord 8002 will go to stand by automatically, ½ hour after the conclusion of a tape cassette.

SETTING UP

Your Beocord 8002 should be positioned on a horizontal surface – either a table or a shelf.

Depth measurement, including cables and connectors is 30 cm; width measurement is 53 cm.

Avoid placing the Beocord 8002 in direct proximity of a radiator – where temperature is considerably higher than that in other parts of the room.



Power mains

Beocord 8002, type 4844 is designed for 220 volt 50–60 Hz operation and can function – without modification – on 190 to 240 volts.

PRESETTING THE ELECTRONIC CLOCK

An electronic clock is incorporated into the design of the Beocord 8002. The purpose of this clock is to start and stop the tape recorder at pre-determined times. Normally, the clock is not visible: if **TIME SET** is pressed the time counter will display actual time. Indication is given in the form of the flashing point located lowest-midway, between the digits. When you connect your Beocord 8002 to the power mains, the clock will start with 00:01. Setting the clock to the actual hour is done as follows: If – for example – your watch shows that the time of day is 13.30: Press **TIME SET** and digits **1 3 3 1**. When your watch shifts to 13.31, press **GO**.

In the event of a power mains failure, reset the electronic clock again. Check the clock reading, press **TIME SET** and conclude by pressing **GO**.

Connecting to Beomaster 8000

Connect cable 6270222 to TAPE 1 socket on the Beomaster 8000. Connect other end of cable to AMPLIFIER socket on the back of the Beocord 8002. Check that the LEVEL switch is at LINE, and the switch on the front of the cassette recorder is at AMPLIF.

Other receivers with DIN plug

Use cable 6270222 with LEVEL switch at DIN.

Phono plugs

The Beocord can also be connected to a receiver or amplifier with RCA phono plugs. Use cable 6270215 with LEVEL switch at LINE. When using the Beocord 8002 in conjunction with other radio receivers or amplifiers, the two outermost pins must be removed. Turn anti-clockwise with a small screwdriver.

MPX filter

The switch on the base of the Beocord should as a rule be switched to OUT. The IN position is designed for recording FM stereo broadcasts from receivers with insufficient multiplex signal muting.

All Beomaster receivers are provided with effective filters so the switch can remain in the OUT position.

MICROPHONE AND AUX Recording microphone

The MIC socket on the front of the Beocord is designed for a stereo microphone with 5 point DIN plug. An adaptor cable type 6271160 can be supplied for a mono microphone with jack plug. Recordings will be mono with the two channels combined. A double adaptor cable type 6271159 can be supplied for stereo recordings using two mono microphones with jack plugs. Microphone data: Sensitivity 0,1 – 3 mV, 400 – 1500 ohms.

AUX input

The same socket may be employed as an auxiliary input – for instance, for copying from another tape recorder. Standard cable type 0961014 is used between the two tape recorders and the switch is placed in AUX. (Sensitivity: 120 mV/1.2 M ohms).

Remote Mains Switch

The programming for tape playback and recording also applies when the Beocord 8002 is used in connection with the Beomaster 8000.

If you wish to use the Beocord 8002 with another radio receiver, you can purchase a Remote Mains Switch, type 4002, which can switch the receiver on and off.


International Guarantee

This Bang & Olufsen product carries a guarantee against defects in workmanship and materials.

It is a national guarantee issued by the Bang & Olufsen Distributors for the country in which the product is purchased initially.

The terms of this guarantee apply principally to the country of origin but will also be met by any authorised Bang & Olufsen dealer in the other countries in which Bang & Olufsen products are officially marketed.

In order to obtain »guarantee« service whilst in a country other than that in which the product was originally purchased, it is essential to ensure that the original Bang & Olufsen guarantee form, which you may claim issued at the purchase of the product, is completed in full and that your copy is presented to the dealer on request for service.



MAINTENANCE AND UPKEEP

Tape head

To ensure pure and clear sound quality, the magnetic heads and capstan axle must be kept free of tape dust.

Use a rinsing fluid designed for this application.

Avoid the use of denatured alcohol; it may contain ingredients hostile to rubber or plastic.

Surfaces

Oily spots that may appear should be removed with a soft, dry cloth.

Teak and rosewood

If wood surfaces seem off-coloured and dry, you might apply a thin layer of teak or rosewood oil – though never more than twice yearly.

For the UK market only.

IMPORTANT

The wires in this mains lead are coloured in accordance with the following code:

Blue: Neutral

Brown: Live

As the colours of the wires in the mains lead of this apparatus may not correspond with the coloured markings identifying the terminals in your plug proceed as follows.

The wire which is coloured blue must be connected to the terminal which is marked with the letter N or coloured black. The wire which is coloured brown must be connected to the terminal which is marked with the letter L or coloured red.

Ensure that your equipment is connected correctly. If you are in any doubt, consult a qualified electrician. This set requires a **3 Amp** fuse in the mains plug.

TECHNICAL DATA	BEOCORD 8002
Type No.	4844
Compact cassette	C46-C60-C90-C120
Tape head	Sendust
Noise reduction	Dolby B
Tape switch	Aut. ferro/chrom/metal
Wow and flutter DIN	<±0.1%
Wow and flutter WRMS	<0.045%
Speed deviation	<±1%
Fast forward and rewind C60	70 sec.
Frequency range metal/chrome/ferric	20–20.000 Hz ±3 dB
Signal-to-noise ratio metal Dolby NR	>68 dB
Signal-to-noise ratio chrome Dolby NR	>66 dB
Signal-to-noise ratio ferric Dolby NR	>64 dB
Signal-to-noise ratio metal	>60 dB
Signal-to-noise ratio chrome	>58 dB
Signal-to-noise ratio ferric	>56 dB
Drivability metal	>– 5 dB
Drivability chrome/ferric	>– 10 dB
Distortion metal	<2%
Channel separation	>35 dB
Erasure	>70 dB
Erase frequency	96 kHz
Radio input DIN/LINE	1 mV/10 kohms – 40 mV/470 kohms
Microphone input	0.1 mV/3 kohms
AUX input	100 mV/1.2 Mohms
Radio output adjustable	1000 mV(500-2000 mV)/ 10 kohms
Headphones	Max. 10 V/56 ohms
Power supply	220 volts
Power frequency	50–60 Hz
Power consumption	Max. 50 watts
Dimensions W×H×D	53×13×30 cm
Weight	7.5 kg

Subject to change without notice

Bang & Olufsen Distributors

ARGENTINA

Aurora S.A.
Paraguay 1102
Buenos Aires 1057

AUSTRALIA

G.R.D. Group Pty. Ltd.
698 Burke Road
Camberwell
Victoria 3124
Phone: (03) 82 - 1256

AUSTRIA

Bang & Olufsen Ges.m.b.H.
1130 Wien
Hietzinger Kai 137a
Phone: (0222) 822671

BAHRAIN

Musicentre
Awal Building
Govt. Road
Manama
Phone: 2-55727

BELGIUM

S.A. Bang & Olufsen Belgium N.V.
Rue Bollinckx, 24
1070 Bruxelles
Phone: 02-520 22 40

CANADA

BSR (Canada) Limited
26 Clairville Drive
Rexdale, Ontario M9V 4B3
Phone: (416) 675-2425

DENMARK

Bang & Olufsen a/s
7600 Struer
Phone: 07/85 45 00

FINLAND

OY Bang & Olufsen AB
Kuortanegaten 1
SF - 00520 Helsingfors 52
Phone: 716400

FRANCE

Bang & Olufsen France S.A.
97-99 Rue Damrémont
75018 Paris
Phone: 01/255 42 01

GERMANY

Beo HiFi-Geräte
Vertriebsges. m.b.H. & Co.
2000 Hamburg 1
Wandalenweg 20
Phone: 040/287469

GREECE

John Ul. Kyriacopoulos & Co.
19 Amerikis Street
Athens 135
Phone: 3627697 - 3606543

HOLLAND

Bang & Olufsen
Nederland B.V.
P.O. Box 36
'S-Graveland
Phone: 035-61824

HONG KONG

The Radio People Ltd.
25, Chatham Road
Kowloon
Phone: (3) 690217

ICELAND

Radiobudin HF
Skipholt 19
105 Reykjavik
Phone: 29800

IRELAND

Peter Dand & Co. Ltd.
111 Clonskeagh Road
Dublin 6
Phone: 21-694433

ISRAEL

Royal Electronics Limited
48 Hanamal Street
Haifa
Phone: 4-672224

ITALY

DITRON S.p.A.
Viale Certosa 138
20156 Milano
Phone: 02-308 56 45

JAPAN

The East Asiatic Co., Ltd.
5th Floor, Nittochi Bldg.
4-1, Kasumigaseki 1-chrome
Chiyoda-ku
Tokyo 100
Phone: (03) 508-9841

JORDAN

Jeme
P.O. Box 1210
Amman
Phone: 62826

KUWAIT

Mohammed Rafie Husain
Marafie & Sons Co.
Ahmed Al-Jebar Street
Safat
Phone: 439719

LUXEMBOURG

S.A. Bang & Olufsen Belgium N.V.
Rue Boffinckx, 24
1070 Bruxelles
Phone: 02-520 22 40

NORWAY

Bang & Olufsen a/s
Ingvald Ludvigsensgate 14
3000 Drammen
Phone: (03) 823790

OMAN

Photocentre
P.O. Box 3115
Ruwi
Phone: 702823

QATAR

Gulf Showroom
P.O. Box 786
Doha
Phone: 24631

SINGAPORE

Guthrie Singapore Private Ltd.
39 Sixth Avenue
Bukit Timah
Singapore 1027
Phone: 662555

SOUTH AFRICA

Teltron (Pty) Ltd.
17 Faraday Street
Village Main
Johannesburg 2000
Phone: 21-0911

SPAIN

ATOMIUM
Avda Felipe II, 12
Madrid 9
Phone: (91) 27 53 873

SWEDEN

Bang & Olufsen Svenska AB
Albygatan 113
17125 Solna
Phone: 08/981340

SWITZERLAND

Bang & Olufsen AG
Kanalstrasse 27
8152 Glattbrugg
Phone: (01) 8100266

UNITED ARAB EMIRATES

Musicentre
P.O. Box 1584
Riqa - Dubai
Phone: 222458

UNITED KINGDOM

Bang & Olufsen
United Kingdom Limited
Eastbrook Road
Gloucester GL4 7DE
Phone: (0452) 21591

USA

Bang & Olufsen of
America Inc.
515 Busse Road
Elk Grove Village
Ill 60007
Phone: (312) 640 - 0660

YUGOSLAVIA

Iskra Commerce
Celovska 122
61000 Ljubljana
Phone: (061) 551093

Bang & Olufsen